



SERVICE END



The Service End is designed for bare neutral messengers, used in the realization of service branches, they are designed to be used on self-supporting cables (ACSR, AAC, AAAC). Service End are partial tension devices and will retain a minimum of 50% rated breaking strength of the cable. Must be firmly attached to the cable at its end point. This product is made of galvanized steel.

Here is a guide to understanding the catalog number. It is divided into 2 parts, ex: 10-SSG, 10 is the length in inches and SSG is for "Service ends".

CABLE		CATALOG		DESCRIPTION		
Dimension A.W.G.	Diameter	PAYER code	Reference	Packaging	Length ± Inch	Color Payer / reference
						1
#6	,169 / ,198	10-SSG		100	10	Blue
#6	,169 / ,198	11-SSG	SG-4500	100	11	Blue
#5	100 / 224	12-SSG	SG-4501	100	12	Green / White
#5	,199 / ,224	12-336	36-4501	100	12	Green/ White
#4	,225 / ,257	13-SSG	SG-4502	100	13	Orange
#3	,258 / ,289	14-SSG	SG-4503	100	14	Black
#2	,290 / ,325	15-SSG	SG-4504	100	15	Red
#1	,326 / ,360	17-SSG	SG-4505	40	17	Blue / Green
1/0	,361 / ,400	19-SSG	SG-4506	40	19	Yellow
2/0	,401 / ,450	21-SGG	SG-4507	40	21	Black / Blue
3/0	,451 / ,510	23-SSG	SG-4508	30	23	Green / Orange
4/0	,511 / ,580	26-SSG	SG-4509	50	26	Orange / Red