


SPLICE

Galvanized for strand A coat




The Splice is a product specially designed to repair or connect a guy wire. Used properly, the splice achieves the maximum strength capacity of the strand when the strand is manufactured to specifications of ASTM-A475 and / or CSA-G12. Once installed, the splice cannot be reused. This standard product is made of galvanized steel class A, grade 180 EHS (CSA-G12 / ASTM-A475). On request, it can be manufactured in class B or in Galfan.

Here is a guide to understanding the catalog number. It is divided into 3 parts, ex: **3/16-27-SJ**, **3/16** is the diameter of the strand, **27** is the length in inches and **SJ** is for "Steel Splices", and **A, B or G (GALFAN)**.

| STRAND | | | CATALOG | | DESCRIPTION | | |
|---------------------------|----------|-------|-------------|-----------|-------------|------------------|--------|
| Diameter± nominal/inch | | | PAYER code | Reference | Packaging | Length ± Inch | Color |
| 3/16 | 7w | 0,195 | 3/16-27-SJA | GLS-2102 | 40 | 27 | Red |
| 7/32 | 7w | 0,216 | 7/32-29-SJA | GLS-2103 | 40 | 29 | Green |
| 1/4 | 3 or 7w | 0,25 | 1/4-35-SJA | GLS-2104 | 40 | 35 | Yellow |
| 9/32 | 7w | 0,285 | 9/32-38-SJA | GLS-2105 | 25 | 38 | Blue |
| 5/16 | 3 or 7w | 0,327 | 5/16-42-SJA | GLS-2106 | 20 | 42 | Black |
| 3/8 | 3 or 7w | 0,358 | 3/8-50-SJA | GLS-2107 | 15 | 50 | Orange |
| 7/16 | 7w | 0,432 | 7/16-56-SJA | GLS-2108 | 10 | 56 | Green |
| 1/2 | 7 or 19w | 0,498 | 1/2-63-SJA | GLS-2109 | 8 | 63 | Blue |
| 9/16 | 7 or 19w | 0,564 | 9/16-70-SJA | GLS-2110 | 5 | 70 | Yellow |

SPLICE

Galvanized for strand B coat




The Splice is a product specially designed to repair or connect a guy wire. Used properly, the splice achieves the maximum strength capacity of the strand when the strand is manufactured to specifications of ASTM-A475 and / or CSA-G12. Once installed, the splice cannot be reused. This standard product is made of galvanized steel class A, grade 180 EHS (CSA-G12 / ASTM-A475). On request, it can be manufactured in class B or in Galfan.

Here is a guide to understanding the catalog number. It is divided into 3 parts, ex: **3/16-27-SJ**, **3/16** is the diameter of the strand, **27** is the length in inches and **SJ** is for "Steel Splices", and **A, B or G (GALFAN)**.

| STRAND | | | CATALOG | | DESCRIPTION | | |
|---------------------------|----------|-------|-------------|-----------|-------------|------------------|--------|
| Diameter± nominal/inch | | | PAYER code | Reference | Packaging | Length ± Inch | Color |
| 3/16 | 7w | 0,195 | 3/16-27-SJB | GLS-1102 | 40 | 27 | Red |
| 7/32 | 7w | 0,216 | 7/32-29-SJB | GLS-1103 | 40 | 29 | Green |
| 1/4 | 3 or 7w | 0,25 | 1/4-35-SJB | GLS-1104 | 40 | 35 | Yellow |
| 9/32 | 7w | 0,285 | 9/32-38-SJB | GLS-1105 | 25 | 38 | Blue |
| 5/16 | 3 or 7w | 0,327 | 5/16-42-SJB | GLS-1106 | 20 | 42 | Black |
| 3/8 | 3 or 7w | 0,358 | 3/8-50-SJB | GLS-1107 | 15 | 50 | Orange |
| 7/16 | 7w | 0,432 | 7/16-56-SJB | GLS-1108 | 10 | 56 | Green |
| 1/2 | 7 or 19w | 0,498 | 1/2-63-SJB | GLS-1109 | 8 | 63 | Blue |
| 9/16 | 7 or 19w | 0,564 | 9/16-70-SJB | GLS-1110 | 5 | 70 | Yellow |

SPLICE

Galvanized for strand G coat, Galfan or Bezinal



The Splice is a product specially designed to repair or connect a guy wire. Used properly, the splice achieves the maximum strength capacity of the strand when the strand is manufactured to specifications of ASTM-A475 and / or CSA-G12. Once installed, the splice cannot be reused. This standard product is made of galvanized steel class A, grade 180 EHS (CSA-G12 / ASTM-A475). On request, it can be manufactured in class B or in Galfan.

Here is a guide to understanding the catalog number. It is divided into 3 parts, ex: **3/16-27-SJ**, **3/16** is the diameter of the strand, **27** is the length in inches and **SJ** is for "Steel Splices", and **A, B or G (GALFAN)**.

| STRAND | | | CATALOG | | DESCRIPTION | | |
|---------------------------|----------|-------|-------------|-----------|-------------|------------------|--------|
| Diameter± nominal/inch | | | PAYER code | Reference | Packaging | Length ± Inch | Color |
| 3/16 | 7w | 0,195 | 3/16-27-SJG | BLS-9102 | 40 | 27 | Red |
| 7/32 | 7w | 0,216 | 7/32-29-SJG | BLS-9103 | 40 | 29 | Green |
| 1/4 | 3 or 7w | 0,25 | 1/4-35-SJG | BLS-9104 | 40 | 35 | Yellow |
| 9/32 | 7w | 0,285 | 9/32-38-SJG | BLS-9105 | 25 | 38 | Blue |
| 5/16 | 3 or 7w | 0,327 | 5/16-42-SJG | BLS-9106 | 20 | 42 | Black |
| 3/8 | 3 or 7w | 0,358 | 3/8-50-SJG | BLS-9107 | 15 | 50 | Orange |
| 7/16 | 7w | 0,432 | 7/16-56-SJG | BLS-9108 | 10 | 56 | Green |
| 1/2 | 7 or 19w | 0,498 | 1/2-63-SJG | BLS-9109 | 8 | 63 | Blue |
| 9/16 | 7 or 19w | 0,564 | 9/16-70-SJG | BLS-9110 | 5 | 70 | Yellow |