

ALUMINUM UNIFORMED ARMOR RODS (NORMAL DUTY) FOR A.C.S.R. AND SMOOTH BODY CONDUCTORS FOR SIMPLE AND DOUBLE SUPPORT

Here is a guide to understanding the catalog number.

It is divided into 3 parts, ex: **TURKEY-40-A**, **TURKEY** is the name of the conductor, **40** is the length in inches and **A** is for Aluminum.

For double support conductors, you can choose the catalog number as follows. EX: **Turkey-40-A** becomes **Turkey-52-A** (40+12 inches) for double support. For double support products, add 12 inches to the length of the catalog number.

CONDUCTOR				CATALOG	DESCRIPTION								
Size A.W.G.	Type	Diameter±		Catalog number	Rod Diameter±		no. per set	Packaging			Length± Inch/centimeter		Color
		Inch	Centimeter		Inch	Centimeter		Units	Dimension	Poids	Inch	Centimeter	
6	A C S R (6/1)	0,198	0,503	TURKEY-40-A	0,121	0,307	7	50			40	101,600	Blue
6	SB 100%	0,182	0,462	BASS-40-A	0,121	0,307	7	50			40	101,600	Blue
6	SB 150%	0,195	0,495	MULLET-40-A	0,121	0,307	7	50			40	101,600	Blue
6	SB 200%	0,200	0,508	HERRING-40-A	0,121	0,307	7	50			40	101,600	Black
6		0,198	0,503	TURKEY-52-A	0,121	0,307	7	50			52	132,080	Blue
4	A C S R (6/1)	0,250	0,635	SWAN-40-A	0,146	0,371	7	50			40	101,600	Orange
4	SB 100%	0,228	0,579	PIKE-40-A	0,146	0,371	7	50			40	101,600	White
4	SB 150%	0,246	0,625	POLLOCK-40-A	0,146	0,371	7	50			40	101,600	Brown
4	SB 200%	0,253	0,6426	FLOUNDER-40-A	0,146	0,371	7	50			40	101,600	Brown
4		0,250	0,635	SWAN-52-A	0,146	0,371	7	50			52	132,080	Orange
2	A C S R (6/1)	0,316	0,803	SPARROW-44-A	0,146	0,371	8	50			44	111,760	Red
2	SB 100%	0,289	0,734	CARP-44-A	0,146	0,371	8	50			44	111,760	Yellow
2	SB 150%	0,310	0,787	HADDOCK-44-A	0,146	0,371	8	50			44	111,760	Purple
2	SB 200%	0,319	0,810	PICKEREL-44-A	0,146	0,371	8	50			44	111,760	Purple
2		0,316	0,803	SPARROW-56-A	1,146	2,911	8	50			56	142,240	Red
1	A C S R (6/1)	0,355	0,902	ROBIN-48-A	0,146	0,371	9	50			48	121,920	Green
1	SB 100%	0,325	0,826	SHAD-48-A	0,146	0,371	8	50			48	121,920	Red
1	SB 150%	0,348	0,884	LAMPREY-48-A	0,146	0,371	9	50			48	121,920	Blue
1		0,355	0,902	ROBIN-64-A	0,146	0,371	9	25			60	152,400	Green
1/0	A C S R (6/1)	0,398	1,011	RAVEN-52-A	0,167	0,424	9	25			52	132,080	Yellow
1/0	SB 100%	0,364	0,925	SOLE-52-A	0,167	0,424	9	25			52	132,080	Green
1/0	SB 150%	0,391	0,993	SCULPIN-52-A	0,167	0,424	10	25			52	132,080	Black
1/0		0,398	1,011	RAVEN-64-A	0,167	0,424	9	25			64	162,560	Yellow
2/0	A C S R (6/1)	0,447	1,135	QUAIL-54-A	0,167	0,424	10	25			54	137,160	Blue
2/0	SB 100%	0,410	1,041	HAKE-54-A	0,167	0,424	10	25			54	137,160	Yellow
3/0	A C S R (6/1)	0,502	1,275	PIGEON-56-A	0,167	0,424	11	20			56	142,240	Orange
3/0	SB 100%	0,460	1,168	CUSK-56-A	0,167	0,424	11	20			56	142,240	Blue
4/0	A C S R (6/1)	0,563	1,430	PENGUIN-60-A	0,182	0,462	11	15			60	152,400	Red
4/0	SB 100%	0,516	1,311	SCUP-60-A	0,182	0,462	11	15			60	152,400	Orange
266,800 cm	A C S R (18/1)	0,609	1,547	WAXWING-64-A	0,182	0,462	12	15			64	162,560	Purple
266,800 cm	A C S R (6/7)	0,633	1,608	OWL-64-A	0,182	0,462	12	15			64	162,560	Yellow
266,800 cm	A C S R (26/7)	0,642	1,631	PARTRIDGE-64-A	0,182	0,462	12	15			64	162,560	Yellow
300,000cm	A C S R (26/7)	0,680	1,727	OSTRICH-68-A	0,204	0,518	12	10			68	172,720	Blue
300,000cm	A C S R (30/7)	0,700	1,778	PIPER-68-A	0,204	0,518	12	10			68	172,720	Blue
336,400cm	A C S R (18/1)	0,684	1,737	MERLIN-68-A	0,204	0,518	12	10			68	172,720	Blue
336,400cm	A C S R (26/7)	0,721	1,831	LINNET-72-A	0,204	0,518	12	10			72	182,880	Green
336,400cm	A C S R (30/7)	0,741	1,882	ORIOLE-72-A	0,204	0,518	13	10			72	182,880	Orange
397,500cm	A C S R (18/1)	0,743	1,887	CHICKADEE-72-A	0,204	0,518	13	8			72	182,880	Orange
397,500cm	A C S R (26/7)	0,783	1,989	IBIS-76-A	0,250	0,635	11	8			76	193,040	Purple
397,500cm	A C S R (30/7)	0,806	2,047	LARK-76-A	0,250	0,635	11	8			76	193,040	Purple

ALUMINUM UNIFORMED ARMOR RODS (NORMAL DUTY) FOR A.C.S.R. AND SMOOTH BODY CONDUCTORS FOR SIMPLE AND DOUBLE SUPPORT

447,000cm	A C S R (26/7)	0,858	2,179	HAWK-78-A	0,250	0,635	12	7			78	198,120	Blue
447,000cm	A C S R (30/7)	0,883	2,243	HEN-78-A	0,250	0,635	12	7			78	198,120	Blue
556,500cm	A C S R (26/7)	0,927	2,355	DOVE-80-A	0,250	0,635	13	7			80	203,200	Green
556,500cm	A C S R (30/7)	0,953	2,421	EAGLE-80-A	0,250	0,635	13	7			84	213,360	White
605,000cm	A C S R (54/7)	0,953	2,421	DUCK-80-A	0,250	0,635	13	7			84	213,360	White
636,000cm	A C S R (54/7)	0,977	2,482	GOOSE-88-A	0,310	0,787	11	4			88	223,520	Yellow
636,000cm	A C S R (26/7)	0,990	2,515	GROSBEAK-92-A	0,310	0,787	11	4			92	233,680	Yellow
636,000cm	A C S R (30/19)	1,019	2,588	EGRET-92-A	0,310	0,787	12	4			92	233,680	Brown
666,600cm	A C S R (54/7)	1,000	2,540	GULL-92-A	0,310	0,787	12	4			92	233,680	Yellow
715,500cm	A C S R (54/7)	1,036	2,631	CROW-96-A	0,310	0,787	12	4			96	243,840	Blue
715,500cm	A C S R (26/7)	1,051	2,670	STARLING-96-A	0,310	0,787	12	4			96	243,840	Blue
715,500cm	A C S R (30/19)	1,081	2,746	REDWING-96-A	0,310	0,787	12	4			96	243,840	Green
795,000cm	A C S R (54/7)	1,093	2,776	CONDOR-100-A	0,310	0,787	11	4			100	254,000	Green
795,000cm	A C S R (16/7)	1,108	2,814	DRAKE-100-A	0,310	0,787	12	4			100	254,000	Orange
795,000cm	A C S R (30/19)	1,140	2,897	MALLARD-100-A	0,310	0,787	13	4			100	254,000	Purple
874,500cm	A C S R (54/7)	1,146	2,911	CRANE-100-A	0,310	0,787	13	4			100	254,000	Purple
900,000cm	A C S R (54/7)	1,162	2,951	CANARY-100-A	0,310	0,787	13	4			100	254,000	Red
954,000cm	A C S R (54/7)	1,196	3,038	CARDINAL-100-A	0,310	0,787	13	4			100	254,000	Red
1,033,500cm	A C S R (54/7)	1,246	3,165	CURLEW-100-A	0,365	0,927	12	4			100	254,000	Black
1,113,000cm	A C S R (54/19)	1,293	3,284	FINCH-100-A	0,365	0,927	12	3			100	254,000	White
1,192,500cm	A C S R (54/19)	1,338	3,399	GRACKLE-100-A	0,365	0,927	13	3			100	254,000	Yellow
1,272,000cm	A C S R (54/19)	1,382	3,510	PHEASANT-100-A	0,365	0,927	13	3			100	254,000	Yellow

SIMPLE AND DOUBLE SUPPORT

CONDUCTOR				CATALOG	DESCRIPTION								
Size A.W.G.	Type	Diameter±		Catalog number	Rod Diameter±		no. per set	Packaging			Length±		Color
		Inch	Centimeter		Inch	Centimeter		Units	Dimension	Poids	Inch	Centimeter	
4	Aluminum (7-wire)	0,232	0,589	ROSE-40-A	0,121	0,307	8	50			40	101,600	brown
4	Aluminum (7-wire)	0,232	0,589	ROSE-52-A	0,121	0,307	8	50			52	132,080	brown
2	Aluminum (7-wire)	0,292	0,742	IRIS-40-A	0,146	0,371	8	50			42	106,680	Purple
2	Aluminum (7-wire)	0,292	0,742	IRIS-54-A	0,146	0,371	8	50			54	137,160	Purple
1	Aluminum (7-wire)	0,328	0,833	PANSY-46-A	0,146	0,371	9	50			46	116,840	Blue
1	Aluminum (7-wire)	0,328	0,833	PANSY-58-A	0,146	0,371	9	50			58	147,320	Blue
1/0	Aluminum (7-wire)	0,368	0,935	POPPY-50-A	0,146	0,371	10	25			50	127,000	Black
1/0	Aluminum (7-wire)	0,368	0,935	POPPY-62-A	0,146	0,371	10	25			62	157,480	Black
2/0	Aluminum (7-wire)	0,414	1,052	ASTER-52-A	0,146	0,371	10	25			52	132,080	Brown
3/0	Aluminum (7-wire)	0,464	1,179	PHLOX-54-A	0,146	0,371	10	25			54	137,160	Green
4/0	Aluminum (7-wire)	0,522	1,326	OXLIP-58-A	0,167	0,424	11	25			58	147,320	Black

ALUMINUM UNIFORMED ARMOR RODS (NORMAL DUTY) FOR A.C.S.R. AND SMOOTH BODY CONDUCTORS FOR SIMPLE AND DOUBLE SUPPORT

266,800cm	Aluminum (17-wire)	0,586	1,488	DAISY-61-A	0,182	0,462	12	20			61	154,940	Black
300,000cm	Aluminum (19-wire)	0,629	1,598	PEONY-61-A	0,182	0,462	12	20			64	162,560	Purple
336,400cm	Aluminum (19-wire)	0,666	1,692	TULIP-66-A	0,182	0,462	13	15			66	167,640	Brown
397,500cm	Aluminum (19-wire)	0,724	1,839	CANNA-72-A	0,204	0,518	12	10			72	182,880	Green
477,000cm	Aluminum (19-wire)	0,793	2,014	COSMOS-76-A	0,250	0,635	11	8			76	193,040	Purple
500,000cm	Aluminum (19-wire)	0,812	2,062	ZINNIA-76-A	0,250	0,635	11	8			76	193,040	Purple
556,500cm	Aluminum (19-wire)	0,856	2,174	DALHIA-78-A	0,250	0,635	12	7			78	198,120	Blue
636,000cm	Aluminum (37-wire)	0,918	2,332	ORCHID-80-A	0,250	0,635	13	7			80	203,200	Green
715,500cm	Aluminum (37-wire)	0,974	2,474	VIOLET-88-A	0,250	0,635	13	7			88	223,520	White
750,00cm	Aluminum (37-wire)	0,995	2,527	PETUNIA-92-A	0,310	0,787	11	4			92	233,680	Yellow
795,000cm	Aluminum (37-wire)	1,026	2,606	ARBUTUS-94-A	0,310	0,787	12	4			94	238,760	Brown
874,500cm	Aluminum (37-wire)	1,077	2,736	ANEMONE-96-A	0,310	0,787	12	4			96	243,840	Green
954,000cm	Aluminum (37-wire)	1,124	2,855	MAGNOLIA-100-A	0,310	0,787	12	4			100	254,000	Orange
1,033,500cm	Aluminum (37-wire)	1,170	2,972	BLUEBELL-100-A	0,310	0,787	13	4			100	254,000	Red

BODY CONDUCTORS FOR SIMPLE AND DOUBLE SUPPORT

CONDUCTOR				CATALOG		DESCRIPTION							
Size A.W.G.	Type	Diameter±		Catalog number	Rod Diameter±		no. per set	Packaging			Length±		Color
		Inch	Centimeter		Inch	Centimeter		Units	Dimension	weight	Inch	Centimeter	
6	A C S R (6/1)	0,198	0,503	TURKEY-30-S	0,086	0,218	9	50			30	76,200	Black
6	SB 100%	0,182	0,462	BASS-30-S	0,086	0,218	9	50			30	76,200	Black
6	SB 150%	0,195	0,495	MULLET-30-S	0,086	0,218	9	50			30	76,200	Black
6	SB 200%	0,200	0,508	HERRING-30-S	0,086	0,218	9	50			30	76,200	Black
6		0,198	0,503	TURKEY-42-S	0,086	0,218	9	50			42	106,680	Black
4	A C S R (6/1)	0,250	0,635	SWAN-40-S	0,086	0,218	10	50			40	101,600	Orange
4	SB 100%	0,228	0,579	PIKE-40-S	0,086	0,218	10	50			40	101,600	Orange
4	SB 150%	0,246	0,625	POLLOCK-40-S	0,086	0,218	10	50			40	101,600	Orange
4	SB 200%	0,253	0,643	FOULNDER-40-S	0,086	0,218	10	50			40	101,600	Orange
4		0,250	0,635	SWAN-52-S	0,086	0,218	10	25			52	132,080	Orange
2	A C S R (6/1)	0,316	0,803	SPARROW-44-S	0,086	0,218	12	25			44	111,760	Red
2	SB 100%	0,289	0,734	CARP-44-S	0,086	0,218	12	25			44	111,760	Red
2	SB 150%	0,310	0,787	HADDOCK-44-S	0,086	0,218	12	25			44	111,760	Red
2	SB 200%	0,319	0,810	PICKEREL-44-S	0,086	0,218	12	25			44	111,760	Red
2		0,316	0,803	SPARROW-56-S	0,086	0,218	12	25			56	142,240	Red
1	A C S R (6/1)	0,355	0,902	ROBIN-48-S	0,086	0,218	13	25			48	121,920	Black
1	SB 100%	0,325	0,826	SHAD-48-S	0,086	0,218	13	25			48	121,920	Black
1	SB 150%	0,348	0,884	LAMPREY-48-S	0,086	0,218	13	25			48	121,920	Black
1		0,355	0,902	ROBIN-60-S	0,086	0,218	13	25			60	152,400	Black
1/0	A C S R (6/1)	0,398	1,011	RAVEN-52-S	0,100	0,254	13	15			52	132,080	Yellow
1/0	SB 100%	0,364	0,925	SOLE-52-S	0,100	0,254	13	15			52	132,080	Yellow
1/0	SB 150%	0,391	0,993	SCULPIN-52-S	0,100	0,254	13	15			52	132,080	Yellow
1/0		0,398	1,011	RAVEN-64-S	0,100	0,254	13	15			64	162,560	Yellow

**ALUMINUM UNIFORMED ARMOR RODS (NORMAL DUTY) FOR A.C.S.R. AND SMOOTH BODY CONDUCTORS FOR SIMPLE AND DOUBLE
SUPPORT**

2/0	A C S R (6/1)	0,477	1,212	QUAIL-54-S	0,120	0,305	14	15			54	137,160	Bleu
2/0	SB 100%	0,410	1,041	HAKE-54-S	0,120	0,305	14	15			54	137,160	Brown
3/0	A C S R (6/1)	0,502	1,275	PIGEON-56-S	0,120	0,305	14	15			56	142,240	Orange
3/0	SB 100%	0,460	1,168	CUSK-56-S	0,120	0,305	14	15			56	142,240	Orange
4/0	A C S R (6/1)	0,563	1,430	PENGUIN-60-S	0,120	0,305	15	10			60	152,400	Red
4/0	SB 100%	0,516	1,311	SCUP-60-S	0,120	0,305	15	10			60	152,400	Red
266,800cm	A C S R (6/7)	0,633	1,608	OWL-64-S	0,140	0,356	15	10			64	162,560	Green
266,800cm	A C S R (26/7)	0,642	1,631	PARTRIDGE-64-S	0,140	0,356	15	10			64	162,560	Green
300,000cm	A C S R (26/7)	0,680	1,727	OSTRICH-68-S	0,160	0,406	14	10			68	172,720	Red
300,000cm	A C S R (30/7)	0,700	1,778	PIPER-68-S	0,160	0,406	15	10			68	172,720	Red
336,400cm	A C S R (27/7)	0,721	1,831	LINNET-72-S	0,160	0,406	15	10			72	182,880	Yellow
336,400cm	A C S R (30/7)	0,741	1,882	ORIOLE-72-S	0,160	0,406	15	10			72	182,880	Yellow