





GUY END / GUY GRIP





The Guy Ends/Dead End are used to brace distribution lines, telecommunication lines and antenna towers. They are produced in standard dimensions of ½ inch (1.27 cm) or less and in conformity with the ASTM A.475 or the CSA G12 standards. The ends and the guys must have the same (left hand) direction. The guy end reaches its maximum tension capacity if the cable is made according to the standard (ASTM A-475 / CSA-G12) grade 180 specifications. During its initial installation, a maximum of three times the guy end may be removed or replaced. However, shorld a problem arise after more than three months of use, a change is necessary. This product is produced in class A steel, grade 180 (CSA-G12 / ASTM-A475) standard or class B and Galfan upon request.

availa ZINC A coated GNA OPTIONS:

ZINC B coated GNB CL = Cable Loop

AL/ZC covered steel (Galfan) GNG



Here is a guide to understanding the catalog number. It is divided into 3 parts, ex: 3/16-20-GN, 3/16 is the diameter of the strand, 20 is the length in inches and GN is for "Guy ends", CL for cable Loop, ex 3/8-35-GNG-CL

STRAND		CATALOG		DESCRIPTION		
Diameter±	Num/wires	PAYER code	Reference	Packaging	length± Inch	Color
3/16	7w	3/16-20-GNB-CL	GDE-1102	50	20	Red
7/32	7w	7/32-22-GNB-CL	GDE-1103	50	22	Green
1/4	3w,7w	1/4-25-GNB-CL	GDE-1104	50	25	Yellow
9/32	7w	9/32-28-GNB-CL	GDE-1105	50	28	Blue
0,02		0,02 20 0.115 02	952 1100	- 00		5100
5/16	3w, 7w	5/16-30-GNB-CL	GDE-1106	50	30	Black
3/8	3w, 7w	3/8-35-GNB-CL	GDE-1107	40	35	Orange
3/0	JW, /W	3/0-33-GNB-GL	GDE-1107	40	33	Orange
7/16	7w	7/16-38-GNB-CL	GDE-1108	25	38	Green
4/0	7 40	4/0.4F OND O	- (-)	45	45	Dive
1/2	7w, 19w	1/2-45-GNB-CL	n/d	15	45	Blue

PAYER Industries Inc. Section 4





MAPLE WIRE SPLICE

Galvanized for wire



The steel splices is a product especially conceived to repair or connect a guy end. Used adequately, the splice reaches its maximum fracture capacity when the cable is made according to standard ASTM-A475 and/or CSA-G12 specifications. Once installed, the splice may not be re-used. This product is produced in class A steel, grade 180 (CSA-G12 / ASTM-A475) standard or class B upon request.

Here is a guide to understanding the catalog number. It is divided into 3 parts, ex: 3/16-27-SJ, 3/16 is the diameter of the strand, 27 is the length in inches and SJ is for "Steel Splices", and A or B Coat

Numéro Catalogue	Description	Couleur	Boîte	Poids lbs/boîte
109-24-SJ	Épissure préformée pour broche #10	Noir	50 jeux de 2	10 lbs
134-26-SJ	Épissure préformée pour broche #9	Orange	50 jeux de 2	12 lbs
156-24-SJ	Épissure préformée pour broche #8	Blanc	50 jeux de 2	14 lbs
3/16-27-SJ	Épissure préformée	Rouge	40 jeux de 2	12 lbs
1/4-35-SJ	Épissure préformée	Jaune	40 jeux de 2	20 lbs

PAYER Industries Inc. Section 15

PAYER Industries Inc. Section 15