


# SPLICE

## Aluminium



The aluminum splices is a product especially conceived to repair or connect a conductor cable or a transmitter cable. Used adequately, the splices reaches its maximum fracture capacity when the cable is made according to standard. Once installed, the splices may not be re-used. This product is produced in aluminum .6201 or .6061.

CONDUCTOR			CATALOG		DESCRIPTION			
Diameter± nominal/inch			PAYER code	Reference	No. Of set	Pack	Length ± Inch	Color
# 6	7w all alu.	,177 / ,184	PLS0106	LS-0106	2	50	21	Purple
# 6	6/1, 7w alloy	,194 / ,202	PLS0108	LS-0108	2	50	22	Blue
# 4	7w all alu.	,229 / ,239	PLS0112	LS-0112	2	50	24	Brown
# 4	6/1, 7/1, 7w alloy	,247 / ,257	PLS0114	LS-0114	2	50	26	Orange
# 3	7w all-alu	,258 / ,270	PLS0115	LS-0115	2	50	26	Green
#3	7w alloy	,271 / ,280	PLS0116	LS-0116	2	50	27	Yellow
# 2	7w all alu.	,290 / ,298	PLS0118	LS-0118	2	50	28	Purple
#2, #3	#2 awac 6/1, #3 awac 5/2	,299 / ,310	PLS0119	LS-0119	2	50	30	Brown
# 2	6/1, 7/1, 7w alloy	,311 / ,325	PLS0120	LS-0120	3	50	31	Red
# 1	7w all-alu	,326 / ,340	PLS0121	LS-0121	3	50	31	Blue
# 1	awac 6/1	,341 / ,351	PLS0122	LS-0122	3	40	33	Orange
# 1	6/1, 7w alloy	,352 / ,367	PLS0123	LS-0123	3	40	34	Green
#1, 1/0	#1 awac 5/2 1/0 7w all alu.	,368 / ,380	PLS0124	LS-0124	3	25	38	Black
1/0	6/1awac, 7w alloy	,381 / ,398	PLS0125	LS-0125	3	25	38	Yellow
2/0	7w all alu.	,414 / ,425	PLS0127	LS-0127	3	20	40	Brown
2/0	6/1, 7w alloy	,444 / ,462	PLS0129	LS-0129	3	20	42	Blue
3/0	7w all alu.	,463 / ,481	PLS0130	LS-0130	3	20	46	Green
3/0	7w alloy, 6/1 awac	,482 / ,503	PLS0131	LS-0131	3	15	46	Orange
3/0, 4/0	3/0 awac 5/2 4/0 7w all alu.	,522 / ,544	PLS0133	LS-0133	3	15	51	Black
4/0	7w alloy, 6/1	,545 / ,567	PLS0134	LS-0134	3	15	52	Red
266,8 mcm	7w-19w-37w all alu	,568 / ,594	PLS0135	LS-0135	3	10	61	Blue
266,8 mcm	18/1	,595 / ,618	PLS0136	LS-0136	3	8	63	Purple
266,8 mcm	26/7	,619 / ,644	PLS0137	LS-0137	3	5	67	Yellow
300 mcm	18/1	,645 / ,671	PLS0138	LS-0138	3	5	69	Brown