


DISTRIBUTION DEAD END

Galvanized steel



The bare electrical conductor steel dead ends are especially conceived to maintain the tension at the end of the main, secondary and subsequent line conductors. A Cable Loop attachment is available for all products upon request. They are produced in class A steel grade 180 (CSA-G12 / ASTM-A475) standard or class B upon request.

Cable			Payer catalog		DESCRIPTION		
Size A.W.G.	Type of cable	Diameter inch Min. / Max	PAYER code	Reference	Packaging	Length± inch	Color
# 6	7w, 2/64s, 3/64s	,229 / ,257	PDG2510	DG-2510	50	18	Orange
# 4, #6	#4 2/64s, #6- 7w,3/64s	,258 / ,289	PDG2511	DG-2511	75	21	Yellow
#4, #6	#4 - 7w, 2/64s #6 - 7w, 2/64s	,290 / ,325	PDG2512	DG-2512	50	24	Red
# 4	7w, 3/64s, 4/64s	,326 / ,364	PDG2513	DG-2513	50	27	Green
#2, #4	#2 - 7w, 3/64s #4- 7w, 5/64s	,365 / ,409	PDG2514	DG-2514	50	26	Yellow
# 2	7w, 4/64s, 5/64s	,410 / ,460	PDG2515	DG-2515	40	28	Blue
#1, 1/0	#1 - 19w, 5/64s 1/0 - 7w, 4/64s	,461 / ,516	PDG2516	DG-2516	25	32	Orange
1/0	19w, 5/64s, 6/64s	,517 / ,577	PDG2517	DG-2517	15	34	Purple
3/0, 4/0	3/0 - 7w, 4/64s 4/0 - 7w, 4/64s	,578 / ,653	PDG2100	DG-2100	15	35	Blue / Black