

DEAD END COATED



The aluminum dead ends with 'Neoprene' are conceived especially for poly-covered conductors. Once installed, these dead ends must not be re-used. They are produced in aluminum .6201 or .6061.



Open Loop



Cable Loop

Size A.W.G.	CABLE		CATALOG		DESCRIPTION		
	Number of wires	Diameter min/max	PAYER code	Reference	Packaging	Length± inch	Color
#6 *	7w, 2/64s	,243 / ,253	PND0500	ND-0500	50	17	Green
#6 *	3/64s,6/1,2/64s	,254 / ,264	PND0501	ND-0501	50	17	Red
#4 *	2/64s	,265 / ,272	PND0502	ND-0502	50	18	Blue
#6 *	7w, 3/64s	,273 / ,284	PND0503	ND-0503	50	18	Orange
#4, #6	#4 - 7w, 2/64s #6 - 6/1, 3/64s	,285 / ,297	PND0100	ND-0100	50	19	Black
#4, #6	#4 - solid, 3/64s #6 - 7w, 4/64s	,298 / ,310	PND0101	ND-0101	50	19	Yellow
#4	7w, 2/64s alloy 6/1, 2/64s	,311 / ,323	PND0102	ND-0102	40	20	Blue
#4, #6	#4 - 7w, 3/64s #6- 7w, 4/64s alloy	,324 / ,338	PND0103	ND-0103	40	20	Orange
#4	7w, 3/64s, alloy 6/1, 3/64s	,339 / ,354	PND0104	ND-0104	40	21	Black
#4	7w, 4/64s	,355 / ,374	PND0105	ND-0105	40	22	Yellow
#4	7w, 4/64s, 5/64s	,375 / ,397	PND0106	ND-0106	40	23	Red
#2	6/1, 7/1, 3/64s	,398 / ,420	PND0107	ND-0107	40	24	Green
#1, #2	#1 - 7w, 3/64s #2 - 7w,4/64s alloy	,421 / ,445	PND0108	ND-0108	25	27	Black
#1, #4	#1 - 7w, 4/64s #4 - 7w, 8/64s	,446 / ,475	PND0109	ND-0109	25	28	Orange
#1, 1/0	#1 - 19w, 5/64s 1/0 - 7w, 4/64s	,476 / ,507	PND0110	ND-0110	25	30	Blue
1/0	19w, 5/64s,6/64s	,508 / ,536	PND0111	ND-0111	25	30	Red
2/0	7w, 19w, 4/64s 6/64s comp	,537 / ,571	PND0112	ND-0112	25	31	Black
2/0, 3/0	2/0- 19w, 5/64s 3/0- 19w, 4/64s	,572 / ,608	PND0113	ND-0113	25	33	Yellow
1/0, 4/0	1/0 - 7w, 8/64s 4/0 - 7w, 4/64s	,609 / ,648	PND0114	ND-0114	25	33	Red
1/0, 4/0	1/0 - 7w, 10/64s 4/0 - 19w, 4/64s	,649 / ,690	PND0115	ND-0115	25	34	Green

DEAD END COATED

CABLE		Diameter		CATALOG	Reference	DESCRIPTION		
Size A.W.G.	Number of wires	min	max	PAYER code		Packaging	Length± inch	Color
266,8 mcm	18/1, 4/64s	,691	,735	PND0116	ND-0116	25	35	Black
3/0	7w, 10/64s	,736	,783	PND0117	ND-0117	15	36	Orange
300 mcm 336 mcm	300- 19w, 5/64s 336- 19w, 5/64s	,784	,834	PND0118	ND-0118	15	38	Blue
300 mcm 350 mcm	300 - 19w, 10/64s 350 - 19w, 5/64s	,835	,888	PND0119	ND-0119	15	40	Black
250 mcm 300 mcm	250- 19w, 10/64s 300- 19w, 10/64s	,889	,945	PND0120	ND-0120	15	42	Yellow
450 mcm 500 mcm	450 - 37w, 6/64s 500 - 37w, 6/64s	,946	1,005	PND0121	ND-0121	15	44	Green
336,4 mcm 450 mcm	336,4- 19w, 12/64s - 37w, 8/64s	450	1,006 / 1,070	PND0122	ND-0122	10	45	Red

* open loop