


# DISTRIBUTION DEAD END

## Aluminium



The bare electrical conductor steel dead ends are especially conceived to maintain the tension at the end of the main, secondary and subsequent line conductors. Cable Loop attachment is available for all products upon request. They are produced in Aluminum (CSA-G12 / ASTM-A475)

Cable			CATALOG		DESCRIPTION		
Size A.W.G.	Type of cable	Diameter inch Min. / Max	PAYER code	Reference	Packaging	Length inch	Color
# 6	6/1 acsr, 7w alu.	,182 / ,203	PDG4554	DG-4554	100	19	Blue
# 4	6/1, 7/1 acsr, 7w alu.	,229 / ,257	PDG4541	DG-4541	100	22	Orange
# 2	6/1, 7/1 acsr, 7w alu.	,290 / ,325	PDG4542	DG-4542	50	24	Red
# 1	6/1 acsr, 7w alu.	,326 / ,364	PDG4543	DG-4543	50	26	Green
1/0	1/0 acsr and alu.	,365 / ,409	PDG4544	DG-4544	50	28	Yellow
2/0	6/1 acsr, 7w alu.	,410 / ,460	PDG4545	DG-4545	40	30	Blue
3/0	6/1 acsr, 7w alu.	,461 / ,516	PDG4546	DG-4546	25	33	Orange
4/0	6/1 acsr, 7w alu.	,517 / ,577	PDG4547	DG-4547	25	35	Red
266,8 mcm 336,4 mcm	18/1 acsr, 19w alu	,578 / ,653	PDG4548	DG-4548	15	37	Black
336,4 mcm 397,5 mcm	18/1 acsr, 19w alu.	,654 / ,739	PDG4549	DG-4549	15	41	Green