

BRACING END



Bracing ends are designed to provide fast and efficient metal building construction. The advantages are many: greater variety of design in buildings, easier assembly and installation on the job, lighter weight and saving in fabrication and labor costs.

Performance: Holding strength is a minimum of 100% of the rated strength of the strand. Bracing ends can be used with a standard small eye, Eye bolt with washer and nut and a length of galvanized steel guy wire. Bracing ends are available in a complete range of sizes to fit all sizes of the guy strand to give the bracing strength required. Bracing ends have a left lay.

Here is a guide to understanding the catalog number. It is divided into 3 parts, ex: **1/4-19,5-MB** , **1/4** is the diameter of the strand, **19,5** is the length in inches and **MB** is for "Bracing ends"

STRAND		Payer Industries		DESCRIPTION			
Diameter±		PAYER code	Reference	Packaging	length± Inch	Rated strenght	Color
1/4	7w	1/4-19,5-MB	BRG-2580	50	19,5	6 650	Yellow
5/16	3w, 7w	5/16-21-MB	BRG-2582	50	21	11 200	Black
3/8	3w, 7w	3/8-26-MB	BRG-2583	50	26	15 400	Orange
7/16	3w, 7w	7/16-30,5-MB	BRG-2584	25	30,5	20 800	Green
1/2	7w, 19w	1/2-34-MB	BRG-2585	25	34	26 900	Blue

