


# SPLICE

## Aluminium



The Splice is a product specially designed to repair or connect a conductor cable or a transmission cable. The splice achieves its maximum breaking strength and conductivity capacity when properly installed. Once installed, the splice cannot be reused. This product is made of 6201 aluminium.

CONDUCTOR		CATALOG		DESCRIPTION				
Diameter± nominal/inch		PAYER code		Reference	No. Of set	Pack	Length ± Inch	Color
# 6	7w all alu.	,177 / ,184	PLS0106	LS-0106	2	50	21	Purple
# 6	6/1, 7w alloy	,194 / ,202	PLS0108	LS-0108	2	50	22	Blue
# 4	7w all alu.	,229 / ,239	PLS0112	LS-0112	2	50	24	Brown
# 4	6/1, 7/1, 7w alloy	,247 / ,257	PLS0114	LS-0114	2	50	26	Orange
# 3	7w all-alu	,258 / ,270	PLS0115	LS-0115	2	50	26	Green
#3	7w alloy	,271 / ,280	PLS0116	LS-0116	2	50	27	Yellow
# 2	7w all alu.	,290 / ,298	PLS0118	LS-0118	2	50	28	Purple
#2, #3	#2 awac 6/1, #3 awac 5/2	,299 / ,310	PLS0119	LS-0119	2	50	30	Brown
# 2	6/1, 7/1, 7w alloy	,311 / ,325	PLS0120	LS-0120	3	50	31	Red
# 1	7w all-alu	,326 / ,340	PLS0121	LS-0121	3	50	31	Blue
# 1	awac 6/1	,341 / ,351	PLS0122	LS-0122	3	40	33	Orange
# 1	6/1, 7w alloy	,352 / ,367	PLS0123	LS-0123	3	40	34	Green
#1, 1/0	#1 awac 5/2 1/0 7w all alu.	,368 / ,380	PLS0124	LS-0124	3	25	38	Black
1/0	6/1awac, 7w alloy	,381 / ,398	PLS0125	LS-0125	3	25	38	Yellow
2/0	7w all alu.	,414 / ,425	PLS0127	LS-0127	3	20	40	Brown
2/0	6/1, 7w alloy	,444 / ,462	PLS0129	LS-0129	3	20	42	Blue
3/0	7w all alu.	,463 / ,481	PLS0130	LS-0130	3	20	46	Green
3/0	7w alloy, 6/1 awac	,482 / ,503	PLS0131	LS-0131	3	15	46	Orange
3/0, 4/0	3/0 awac 5/2 4/0 7w all alu.	,522 / ,544	PLS0133	LS-0133	3	15	51	Black
4/0	7w alloy, 6/1	,545 / ,567	PLS0134	LS-0134	3	15	52	Red
266,8 mcm	7w-19w-37w all alu	,568 / ,594	PLS0135	LS-0135	3	10	61	Blue
266,8 mcm	18/1	,595 / ,618	PLS0136	LS-0136	3	8	63	Purple
266,8 mcm	26/7	,619 / ,644	PLS0137	LS-0137	3	5	67	Yellow
300 mcm	18/1	,645 / ,671	PLS0138	LS-0138	3	5	69	Brown