

DISTRIBUTION DEAD END

Aluminium



Distribution Dead End is designed for a bare or sheathed electrical conductor, specially designed to holding strength at the conductor end of a primary, secondary, or subsequent line. Distribution Dead End are designed with an open loop except for drivers over .563 " these will have a cabled loop. This product is made of 6201 aluminum.

Cable			CATALOG		DESCRIPTION		
Size A.W.G.	Type of cable	Diameter inch Min. / Max	PAYER code	Reference	Packaging	Length± inch	Color
# 6	6/1 acsr, 7w alu.	,182 / ,203	PDG4554	DG-4554	100	19	Blue
# 4	6/1, 7/1 acsr, 7w alu.	,229 / ,257	PDG4541	DG-4541	100	22	Orange
# 2	6/1, 7/1 acsr, 7w alu.	,290 / ,325	PDG4542	DG-4542	50	24	Red
# 1	6/1 acsr, 7w alu.	,326 / ,364	PDG4543	DG-4543	40	26	Green
1/0	1/0 acsr and alu.	,365 / ,409	PDG4544	DG-4544	40	28	Yellow
2/0	6/1 acsr, 7w alu.	,410 / ,460	PDG4545	DG-4545	40	30	Blue
3/0	6/1 acsr, 7w alu.	,461 / ,516	PDG4546	DG-4546	25	33	Orange
4/0	6/1 acsr, 7w alu.	,517 / ,577	PDG4547	DG-4547	25	35	Red
266,8 mcm 336,4 mcm	18/1 acsr, 19w alu	,578 / ,653	PDG4548	DG-4548	15	37	Black
336,4 mcm 397,5 mcm	18/1 acsr, 19w alu.	,654 / ,739	PDG4549	DG-4549	15	41	Green